TAWI

PRO80 electric lifter

User friendly control panel - emergency stop

- service indicator



Hand control

Detachable for optimal ergonomic steering.

- Flexible solution for lifting and transporting everything from reels to boxes in an ergonomic and efficient manner.
- Available in three mast sizes; S, M and L.
- The lifter is available in stainless steel, equipped with a white FDA approved cover, ideal for food manufacturing and pharmaceutical industry
- SafeDrive ensures that if a tool hits an object during lowering, it will stop immediately.
- The lifter is belt driven, resulting in safe, quiet and smooth oil free drive.
- With our wide selection of tools and accessories, the PRO80 can be optimized for your needs.
 Standard tools and accessories are presented on the following pages.

Contact your sales representative for bespoke solutions.


Technical specifications


Description	Specifications
PRO80S / PRO80M /PRO80L PRO80SSS / PRO80MSS / PRO80LSS	89200 / 89210 /89220 89205 / 89215 / 89225
Lifting capacity	80 kg
Stroke	850 / 1400 / 1950 mm
Weight of unit	46 / 50 / 53 kg
Total height of unit	1440 / 1990 / 2540 mm
Battery charger	100-240V, grounded 50-60 Hz
Battery	2x12V 7Ah
Watt	40 W
Lifts per charge	80 kg x 1m x 100 times
Up and down motions	Hand control (two speed)
Front wheels	Swiveling
Brake system	Central brake with directional lock
Overload protection	Incorporated in circuit load
IP-rating	IP24
Lifting speed fast/slow	0,1m/s / 0,05m/s
Adjustable legs	Width adjustable by 150 mm per leg


0.000 1,000




Load diagram







All measures are LxWxH





All measures are LxWxH

Ladder

Fold-up ladder, optimal for pushing goods from the tool onto a shelf. This ergonomic three step ladder can be mounted on both sides of the lifter.

Art. 890692






Quickload

This feature for smooth and precise positioning of load saves valuable time and effort for the operator. Positioning is conveniently controlled with the detachable hand control.

Art. 890500



V-block with rotation plate

A v-block on your platform is a flexible and cost efficient solution for handling all types of reels. The rotation plate is suitable for all stainless steel platforms and enables effortless rotation of the v-block. The v-block can also be used without rotation plate.

 $Rotation \ plate \ Art. \ 890640 \\ V-block \ Art. \ 890641, \ block \ length \ 380 \ mm, for reels up to \emptyset 600 \ mm$



Quick coupling

With a quick coupling, switching between different tools is quick and simple, for efficient handling of various goods.

> Art. 892691, sleigh half Art. 892692, tool half

SmartPack

Extend working hours with a detachable battery pack including charger.

Art. 892400





Articulating adapter

Enables easy articulation of tools, adding flexibility to your lifter. The adapter can be mounted between all types of tools.

Art. 892697

ESD wheels

Ensure safety with ESD wheels when electrostatic discharge is not allowed, e.g. in environments where electrical components are assembled.

Art. 890692





Roll kit for platform

Goods are safely rolled onto the lifter with a roll kit attached to the platform.

Fits platforms 892610 and 892611.

Art. 890644 steel roll Ø40x400 mm Art. 890645 plastic roll Ø40x400 mm Art. 890646 steel roll Ø40X600 mm Art. 890647 plastic roll Ø40x600 mm